## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Р

Supplier's address: SERVICE QUALITE, RADIO LONDRES, 33130 BEGLES, FR

Model identifier: 7724580

Lighting tochnology used.	LED	Non directional or	NDIC			
Lighting technology used:	LED	Non-directional or	NDLS			
		directional:				
Light source cap-type	LED intégrée					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light	No			
		source (CLS):				
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						
Parameter	Value	Parameter	Value			

Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consur mode (kWh/10 up to the neares	00 h), rounded	20	Energy efficiency class	F			
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	2 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 700			
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	20,2	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00			
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	83			
Outer dimen-	Height	140	Spectral power dis-	See image			
sions without	Width	125	tribution in the	in last page			
separate con- trol gear, light- ing control	Depth	55	range 250 nm to 800 nm, at full-load				

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,348			
		nates (x and y)	0,360			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	3	Survival factor	0,98			
the lumen maintenance factor	0,70					

(a)'-': not applicable; (b)'-': not applicable;

